


SURFACE MOUNT CRYSTAL CLOCK OSCILLATOR FCXO-03L



Actual size

Specifications

Item	Standard specifications		
Frequency range(MHz)	1.5 to 60.0		
Frequency tolerance (ppm)(at 25°C)	±15, ±20, ±30, ±50, ±100		
Storage temperature range(°C)	-40 to +85		
Operating temperature range(°C)	-10 to +60	-20 to +70	-40 to +85
Frequency versus temperature characteristics (ppm) (Refer to 25°C)	±30 ±50 ±100	±30 ±50 ±100	±50 ±100
Supply voltage(V)	3.3±0.33, 3.0±0.3, 2.5±0.25		
Current consumption (mA)	6(Typ.), 15(Typ.) (Depends on frequency and fan out)		
Output level	CMOS, TTL		
Symmetry(%)	50±10, 50±5		

"Stand-by" CTRL table

Stand-by	Output
"H"	Output enabled.
"L"	Oscillation stop and High impedance output.


- Bypass capacitor should be connected between V_{DD} and GND due to the stabilized operation for the crystal oscillator.
- Please consult us for customized specifications.
- All specifications and markings subjected to change without notice.

Features

- Compact design (5.0mm×3.2mm×1.2mm Max., Weight : 0.07g).
- Resin sealed ceramic package assures extreme accuracy and high reliability.
- Lead-free soldering is available.
- Applications : Laptop PC, DSC, DVC, W-LAN


Dimensions

Unit:mm



Taping

Unit:mm



RIVER RIVER ELETec CORPORATION
URL <http://www.river-ele.co.jp>

Head Office 2-1-1 Fujimigaoka Nirasaki Yamanashi Japan
Phone 81-551-22-1211 Fax 81-551-22-6645
Tokyo Office 4-40-14 Nishishinjuku Shinjuku-ku Tokyo Japan
Phone 81-3-3377-5444 Fax 81-3-3374-2865
Osaka Office Phone 81-6-6998-4888 Fax 81-6-6998-4899

River Electronics(Singapore)Pte.Ltd Phone 65-6258-7874 Fax 65-6258-7366
Taiwan River Co.,Ltd. Phone 886-2-8988-2811 Fax 886-2-2983-4785
Xi'an River Electronics Corporation Phone 86-29-88697274 Fax 86-29-88635134