

TOSHIBA BIPOLAR LINEAR INTEGRATED CIRCUIT SILICON MONOLITHIC


TA4101F

UHF VHF MIX APPLICATION

FEATURES



- Double Balance circuit

PIN ASSIGNMENT (TOP VIEW)



- 1. IF OUT
- 2. V_{CC}
- 3. OSC IN
- 4. Base
- 5. Base
- 6. Base
- 7. GND
- 8. Collector

MARKING



SSOP8-P-0.65
Weight : 0.02g (Typ.)

MAXIMUM RATING (Ta = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Supply Voltage	V _{CC}	6	V
Total Power Dissipation	P _D (*)	300	mW
Operating Temperature	T _{opr}	- 40~85	°C
Storage Temperature Range	T _{stg}	- 55~125	°C

(*) When mounted the glass epoxy board of 2.5cm² × 1.6t

ELECTRICAL CHARACTERISTICS (Ta = 25°C)


CHARACTERISTIC	SYMBOL	TEST CIR-CUIT	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Circuit Current	I _{CC}	—	V _{CC} = 5V	3.9	5.7	7.5	mA
MIXER Gain	G _{MIX}	1	V _{CC} = 5V, (*)	- 6.0	- 3.5	—	dB
MIXER NOISE Figure	NF _{MIX}	1	V _{CC} = 5V, (*)	—	9.0	12.0	dB
Maximum Output Level	P _o	1	V _{CC} = 5V, (*)	- 12	- 9	—	dBmW

(*) : f_{RF} = 800MHz, f_{LO} = 860MHz (0dBm), I_F = 60MHz


961001EBA2







- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The products described in this document are subject to foreign exchange and foreign trade control laws.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

MEASUREMENT CIRCUIT 1.





EQUIVALENT CIRCUIT





OUTLINE DRAWING
SSOP8-P-0.65

Unit : mm



Weight : 0.02g (Typ.)