

形名	社名	最大定格								順方向特性				逆方向特性				Ct (pF)		trr (ns)		その他の特性等	外形				
		V <sub>RRM</sub>	V <sub>R</sub>	I <sub>FM</sub>	T条件	I <sub>o, I<sub>FM</sub></sub>	T条件	I <sub>FSM</sub>	T条件	V <sub>Fmax</sub>	測定条件		I <sub>Rmax</sub>	測定条件		typ	max	typ	max								
		(V)	(V)	(mA)	(°C)	(mA)	(°C)	(A)	(°C)	(V)	I <sub>F</sub> (mA)	T(°C)	(μA)	V <sub>R</sub> (V)	T(°C)												
HSM112WK	日立	8				30*				0.8	1			0.1	5										1.2間と1.3間は異なるが1付ト	610D	
HSM113WK	日立	20				100				1	10			0.1	5										VP1~3間0.35Vmax, 2~3間1.8Vmax	610D	
HSM123	日立	85	80	300		100				1.2	100			0.1	80			1	4			3			2素子直列	610F	
HSM124S	日立	85	80	300		100				1.2	100			0.01	80			4	4			100				610F	
HSM221C	日立	85	80	300		100				1.2	100			0.1	80			2	2			3				610A	
HSM223C	日立	85	80	300		100				1.2	100			0.1	80								3				610E
HSM402S	日立			100		50				1	10			0.1	100							2.4	*				610F
HSM402WK	日立			100		50				1	10			0.1	100							2.4	2.7	*			610D
HSM2692	日立			35		100*				1	10			0.01	25							1.2					610A
HSM2693A	日立			35		100				1	10			0.05	25							1.2					610D
HSM2694	日立			35						1	10			0.01	25							1.2					610C
HSM2836C	日立	85	80	300		100				1.2	100			0.1	80							4		20			610C
HSM2838C	日立	85	80	300		100				1.2	100			0.1	80							2		3			610D
HSS81	日立	200	150	625		150				1	100			0.2	150			1.5						100			79F
HSS82	日立	250	200	625		150				1	100			0.2	200			1.5						100			79F
HSS83	日立	300	250	625		150				1	100			0.2	250			1.5						100			79F
HSS104	日立	40	35	300		110				1.2	100			0.5	35							3		3			79F
HSS271	日立	60	55	360		120		0.4		1.2	100			0.5	55							3		4			79F
HSS400J	日立			100		100				1	10			0.1	100							3					79F
HSS401J	日立			100		100				1	10			0.1	100							1.5					79F
HSS402J	日立			100		100				1	10			0.1	100							2.4					79F
HSS277	日立			35						1.2	400			0.5	38							1.2					420C
* HV-08SS	サンケン	3000				2		0.5		16	10			1	3000							1		180			260A
* HV-06SS	サンケン	6000				2		0.5		26	10			1	6000							1		180			260B
* HV-08	サンケン	8000				1		2		16	10			1	8000			1					500			260B	
* HV-08SS	サンケン	8000				2		0.5		36	10			1	8000							1		180			260B
HVM14	日立		50			50				1	50			0.1	50			0.25									610A
HVM14S	日立		50			50				1	50			0.1	50			0.25									610F
HVM14SR	日立		50			50				1	50			0.1	50			0.25									610G
HVM121WK	日立		100			50*				1.1	50			0.1	30			0.7									610D
* HVT-15SS	サンケン	11k				2		1		32	10			1	11k			0.6						180			43C
* HVT-20SS	サンケン	14k				2		1		42	10			1	14k			0.6						180			43C
* HVT-25SS	サンケン	17k				2		1		52	10			1	17k			0.6						180			43C
* HVT-30S	サンケン	18k				2		3		35	10			1	18k			0.6						500			43E
* HVT-30SS	サンケン	20k				2		1		60	10			1	20k			0.6						200			43D
HVU187	日立		60			50				1	10			0.1	60							2.4					420C
LPB01	三洋	90	80	480		150				1.2	100			0.5	80							3		4			357F
LPB01L	三洋	55	50	480		150				1.2	100			0.5	50							3		4			357F
* LS53	日電	35	30	300		100				1	30			0.1	30			3	6			20	100				357A
* LS54	日電	75	50	300		100				1	30			0.1	50			3	5			20	100				357A
* LS55	日電	100	75	300		100				1	30			0.1	75			3	4			20	100				357A
* LS953	日電	35	30	300		100				1	30			0.1	30			2	4			2	3				357A
* LS954	日電	75	50	300		200				1	100			0.1	50			2	3.5			2	3				357A
* LS955	日電	100	75	600		200				1	150			0.1	75			2	3			2	3				357A
MA1U152A	松下	80	80	225		100*				1.2	100			0.1	75			2						3			495B

