



TND721MH5

 — Excellent Power Device

IGBT Driver

Features

- Buffer type.
- Monolithic structure (Adoption of CMOS process).
- Allows simplified configuration of driver circuit.
- Compatible TTL / CMOS (Under $V_{IH}=2.0V$, at $V_{DD}=2.5$ to $5.5V$).

Specifications

Absolute Maximum Ratings at $T_a=25^\circ C$ (All voltage parameters are voltage referenced to GND)

Parameter	Symbol	Conditions	Ratings	Unit
Supply Voltage	V_{DD}		-0.3 to +7.5	V
Input Voltage	V_{IN}		-0.3 to $V_{DD}+0.3$	V
Output Voltage	V_{OUT}		-0.3 to $V_{DD}+0.3$	V
Allowable Power Dissipation	P_D	Mounted on a ceramic board (600mm ² X0.8mm)	0.8	W
Junction Temperature	T_J		-55 to +150	°C
Storage Temperature	T_{stg}		-55 to +150	°C

Recommended Operating Conditions at $T_a=25^\circ C$ (All voltage parameters are voltage referenced to GND)

Parameter	Symbol	Conditions	Ratings	Unit
Supply Voltage	V_{DD}		2.5 to +5.5	V
Input Voltage	V_{IN}		0 to V_{DD}	V
Output Voltage	V_{OUT}		0 to V_{DD}	V
Operating Temperature	T_{opr}		-40 to +85	°C

Electrical Characteristics (AC) at $T_a=25^\circ C$, $V_{IN}=2.5V$ to V_{DD} , $C_L=5000pF$

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Turn-ON Rise Time	t_r	$V_{DD}=5V$		500	1000	ns
		$V_{DD}=2.5V$		1200	2000	ns
Turn-OFF Fall Time	t_f	$V_{DD}=5V$		500	1000	ns
		$V_{DD}=2.5V$		1400	2000	ns
Turn-ON Delay Time	$t_d(on)$	$V_{DD}=5V$		150	500	ns
		$V_{DD}=2.5V$		300	1000	ns
Turn-OFF Delay Time	$t_d(off)$	$V_{DD}=5V$		500	1000	ns
		$V_{DD}=2.5V$		1200	2000	ns

Marking : XL

■ Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.

■ SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO products described or contained herein.

TND721MH5


Electrical Characteristics (DC) at Ta=25°C, VDD=2.5V to 5.5V

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Input High Level Voltage	V _{IH}		2.0			V
Input Low Level Voltage	V _{IL}				1.0	V
Input High Level Leak Current	I _{IN+}	V _{IN} =V _{DD}			100	μA
Input Low Level Leak Current	I _{IN-}	V _{IN} =0			1	μA
Standby Supply Current	I _{DD}	V _{IN} =0 or V _{DD}			500	μA
Output "H" Load Short Circuit Pulsed Current	I _{O+}	V _{DD} =5V, V _{OUT} =0, C _L =5000pF		50		mA
		V _{DD} =2.5V, V _{OUT} =0, C _L =5000pF		10		mA
Output "L" Load Short Circuit Pulsed Current	I _{O-}	V _{DD} =5V, V _{OUT} =V _{DD} , C _L =5000pF		50		mA
		V _{DD} =2.5V, V _{OUT} =V _{DD} , C _L =5000pF		10		mA


Package Dimensions

unit : mm


2220











Block Diagram











Switching Time Waveform Definition










TND721MH5



TND721MH5



TND721MH5



- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of January, 2005. Specifications and information herein are subject to change without notice.