

FIXED ATTENUATORS

50 Ω

Surface Mount

1W MINIATURE CERAMIC 1 to 30 dB, DC to 7000 MHz



PAT

MODEL NO. ◆	FREQ. RANGE (MHz) f_L - f_U	ATTENUATION (dB) FLATNESS, Max.			VSWR (:1) Max.			POWER (W)	CASE STYLE Note B	CON- NECT- ION	PRICE \$ Qty. (10-49)	
		Nom.	\underline{L}	\underline{M}	\underline{U}	\underline{L}	\underline{M}					\underline{U}
PAT-1	DC-7000	1±0.2	0.3	0.4	0.7	1.2	1.3	1.4	1	AF320	hl	2.95
PAT-2	DC-7000	2±0.2	0.3	0.5	0.9	1.2	1.3	1.4	1	AF320	hl	2.95
PAT-3	DC-7000	3±0.3	0.3	0.5	0.9	1.2	1.3	1.4	1	AF320	hl	2.95
PAT-4	DC-7000	4±0.3	0.3	0.5	0.9	1.2	1.3	1.4	1	AF320	hl	2.95
PAT-5	DC-7000	5±0.3	0.3	0.5	1.0	1.2	1.3	1.4	1	AF320	hl	2.95
PAT-6	DC-7000	6±0.3	0.3	0.5	1.1	1.2	1.3	1.4	1	AF320	hl	2.95
PAT-7	DC-7000	7±0.3	0.4	0.6	1.3	1.3	1.4	1.5	1	AF320	hl	2.95
PAT-8	DC-7000	8±0.4	0.4	0.6	1.5	1.3	1.4	1.5	1	AF320	hl	2.95
PAT-9	DC-7000	9±0.4	0.4	0.6	1.7	1.3	1.4	1.5	1	AF320	hl	2.95
PAT-10	DC-7000	10±0.4	0.4	0.6	1.7	1.3	1.4	1.5	1	AF320	hl	2.95
PAT-12	DC-7000	12±0.6	0.5	0.6	1.8	1.3	1.4	1.5	1	AF320	hl	2.95
PAT-15	DC-7000	15±0.6	0.5	0.7	2.4	1.3	1.4	1.5	1	AF320	hl	2.95
PAT-20	DC-7000	20±1.3	0.5	0.7	2.6	1.4	1.4	1.5	1	AF320	hl	2.95
PAT-30	DC-7000	30±1.7	0.4	0.9	2.8	1.4	1.4	1.5	1	AF320	hl	2.95

\underline{L} = DC-1000 MHz

\underline{M} = DC-2500 MHz

\underline{U} = DC- f_U

features

- low-cost ceramic package
- wideband DC-7 GHz frequency coverage
- excellent VSWR throughout entire band
- miniature size


marking code:

2 digits for nominal
attenuation value.

examples: 03 for PAT-3, 20 for PAT-20

NOTES:

- ◆ PAT models, aqueous washable
- A. Environmental specifications and re-flow soldering informations available in General Information Section.
- B. Units are non-hermetic unless otherwise noted. For details on case dimensions & finishes see :Case Styles & Outline Drawings".
- C. Prices and specifications subject to change without notice.
 1. RF power at 25° C case temp.: 1 Watt.
 2. Attenuation and VSWR at 25° C case temp.



*0 dB on flatness graph corresponds to actual low frequency attenuation value.

NSN GUIDE

MCL NO. NSN

PAT-3	5985-01-460-6040
PAT-6	5985-01-460-6042
PAT-10	5985-01-460-6045
PAT-15	5985-01-460-6043

designers kits available

KIT No.	No. of Units in KIT	Description	Price \$ per KIT
K1-PAT	20	4 of each: PAT-3,6,10,15,20	49.95

pin connections

see case style outline drawings

PORT	hl
INPUT	1
OUTPUT	3
GND	2,4



Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010

ISO 9001 CERTIFIED

Coaxial, 50 Ω, N-type

½W 1 to 20 dB, DC to 6000 MHz

NEW!



UNAT

MODEL NO.	FREQ. RANGE (MHz) f _l -f _u	ATTENUATION** (dB)					VSWR (:1)					POWER* (W)	CASE STYLE Note B	PRICE \$ Qty. (1-9)
		Nom.	FLATNESS***				L ₁		M ₁		U ₁			
			L ₁ Typ.	M ₁ Typ.	U ₁ Typ.	R Typ.	Typ.	Max.	Typ.	Max.	Typ.			
UNAT-1	DC-6000	1±0.3	0.20	0.15	0.10	0.45	1.05	1.20	1.10	1.43	1.40	0.5	FF779	15.95
UNAT-2	DC-6000	2±0.3	0.20	0.25	0.15	0.50	1.07	1.20	1.22	1.43	1.50	0.5	FF779	15.95
UNAT-3	DC-6000	3±0.3	0.20	0.10	0.10	0.35	1.05	1.20	1.22	1.43	1.50	0.5	FF779	15.95
UNAT-4	DC-6000	4±0.3	0.15	0.15	0.10	0.40	1.05	1.20	1.10	1.43	1.50	0.5	FF779	15.95
UNAT-5	DC-6000	5±0.3	0.15	0.15	0.10	0.35	1.05	1.20	1.10	1.43	1.50	0.5	FF779	15.95
UNAT-6	DC-6000	6±0.3	0.15	0.15	0.15	0.40	1.05	1.20	1.20	1.43	1.50	0.5	FF779	15.95
UNAT-7	DC-6000	7±0.3	0.10	0.10	0.15	0.20	1.05	1.20	1.10	1.43	1.50	0.5	FF779	15.95
UNAT-8	DC-6000	8±0.3	0.10	0.10	0.10	0.10	1.05	1.20	1.10	1.43	1.50	0.5	FF779	15.95
UNAT-9	DC-6000	9±0.3	0.15	0.10	0.10	0.15	1.05	1.20	1.10	1.43	1.50	0.5	FF779	15.95
UNAT-10	DC-6000	10±0.3	0.10	0.20	0.20	0.40	1.15	1.35	1.20	1.50	1.50	0.5	FF779	15.95
UNAT-12	DC-6000	12±0.3	0.15	0.20	0.15	0.35	1.15	1.25	1.20	1.80	1.80	0.5	FF779	15.95
UNAT-15	DC-6000	15±0.3	0.20	0.35	0.20	0.60	1.15	1.43	1.20	1.80	1.70	0.5	FF779	15.95
UNAT-20	DC-6000	20±0.3	0.25	0.45	0.40	0.75	1.15	1.25	1.20	1.43	1.50	0.5	FF779	15.95

L₁ = DC-3000 MHz

M₁ = 3000 - 4500 MHz

U₁ = 4500 - 6000 MHz

R = DC-f_u

features

- wideband coverage, DC to 6000 MHz
- rugged construction
- 0.5 watt rating
- off-the-shelf availability
- very low-cost
- patent pending

applications

- impedance matching
- signal level adjustment

NOTES:

* 0.5 watt at 70°C ambient derate linearly 0.015W/°C above 70°C.

** Attenuation varies by 0.3 dB max. over temperature.

*** Flatness= variation overband divided by 2

A. General Quality Control Procedures, Environmental Specifications, Hi-Rel and MIL description are given in General Information (Section 0).

B. Connector types and case mounted options, case finishes are given in section 0, see "Case styles & outline drawings".

C. Prices and specifications subject to change without notice.

1. Operating and storage temperature: -40°C to 100°C



The Design Engineers Search Engine

Provides Actual Data Instantly
At: <http://www.minicircuits.com>

In Stock... Immediate Delivery

For Custom Versions Of Standard Models
Consult Our Applications Dept.

