


Surface Mount, Molded Inductor



FEATURES

- Molded construction provides superior strength and moisture resistance
- Tape and reel packaging for automatic handling, 2000/reel, EIA 481
- Printed marking
- Compatible with vapor phase and infrared reflow soldering
- 100 % lead (Pb)-free and RoHS compliant



STANDARD ELECTRICAL SPECIFICATIONS

IND. (μH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED* DC CURRENT (mA)
0.010	± 20 %	50	50.0	1000	0.20	450
0.012	± 20 %	50	50.0	1000	0.20	450
0.018	± 20 %	50	50.0	1000	0.20	450
0.022	± 20 %	50	50.0	1000	0.20	450
0.027	± 20 %	50	50.0	1000	0.20	450
0.033	± 20 %	50	50.0	1000	0.30	450
0.039	± 20 %	50	50.0	1000	0.30	450
0.047	± 20 %	50	50.0	1000	0.30	450
0.056	± 20 %	40	50.0	900	0.35	450
0.068	± 20 %	40	50.0	800	0.35	450
0.082	± 20 %	40	50.0	700	0.40	450
0.10	± 20 %	30	25.2	650	0.32	450
0.12	± 20 %	30	25.2	600	0.30	450
0.15	± 20 %	30	25.2	500	0.30	450
0.18	± 20 %	30	25.2	400	0.35	450
0.22	± 20 %	30	25.2	350	0.40	450
0.27	± 20 %	30	25.2	300	0.45	450
0.33	± 20 %	30	25.2	250	0.55	430
0.39	± 20 %	30	25.2	220	0.70	380
0.47	± 10 %	30	25.2	190	0.80	355
0.56	± 10 %	30	25.2	170	1.20	285
0.68	± 10 %	30	25.2	150	1.40	270
0.82	± 10 %	30	25.2	140	1.60	250
1.0	± 10 %	50	7.96	100	0.50	450
1.2	± 10 %	50	7.96	80.0	0.55	430
1.5	± 10 %	50	7.96	70.0	0.60	410
1.8	± 10 %	50	7.96	60.0	0.65	390
2.2	± 10 %	50	7.96	55.0	0.70	380
2.7	± 10 %	50	7.96	50.0	0.75	370
3.3	± 10 %	50	7.96	45.0	0.80	355
3.9	± 10 %	50	7.96	40.0	0.90	330
4.7	± 10 %	50	7.96	35.0	1.00	315
5.6	± 10 %	50	7.96	33.0	1.10	300
6.8	± 10 %	50	7.96	27.0	1.20	285
8.2	± 10 %	50	7.96	25.0	1.40	270
10.0	± 10 %	50	2.52	20.0	1.60	250
12.0	± 10 %	50	2.52	18.0	2.00	225
15.0	± 10 %	50	2.52	17.0	2.50	200
18.0	± 10 %	50	2.52	15.0	2.80	190
22.0	± 10 %	50	2.52	13.0	3.20	180
27.0	± 10 %	50	2.52	12.0	3.60	170
33.0	± 10 %	50	2.52	11.0	4.00	160
39.0	± 10 %	50	2.52	11.0	4.50	150
47.0	± 10 %	50	2.52	10.0	5.00	140
56.0	± 10 %	50	2.52	9.0	5.50	135
68.0	± 10 %	50	2.52	9.0	6.00	130
82.0	± 10 %	50	2.52	8.0	7.00	120
100.0	± 10 %	40	0.79	8.0	8.00	110
120.0	± 10 %	40	0.79	6.0	8.00	110
150.0	± 10 %	40	0.79	5.0	9.00	105
180.0	± 10 %	40	0.79	5.0	9.50	102
220.0	± 10 %	40	0.79	4.0	10.0	100
270.0	± 10 %	40	0.79	4.0	12.0	92
330.0	± 10 %	40	0.79	3.5	14.0	85
390.0	± 10 %	40	0.79	3.0	16.0	80
470.0	± 10 %	40	0.79	3.0	26.0	62
560.0	± 10 %	30	0.79	3.0	30.0	50
680.0	± 10 %	30	0.79	3.0	30.0	50
820.0	± 10 %	30	0.79	2.5	35.0	50
1000.0	± 10 %	30	0.25	2.5	40.0	30

ELECTRICAL SPECIFICATIONS

Inductance Range: 0.010 μH to 1000 μH
Inductance Tolerance: ± 20 % for 0.010 μH to 0.39 μH
 ± 10 % for 0.47 μH to 1000 μH standard
 ± 10 %, ± 5 %, ± 3 % available


Temperature Range: - 55 °C to + 125 °C

Coilform Material: Non-magnetic for 0.010 μH to 0.82 μH
 Powdered Iron for 1.0 μH to 120 μH. Ferrite for 150 μH to 1000 μH

TEST EQUIPMENT

- H/P 4342A Q meter with Vishay Dale test fixture or equivalent
- H/P 4191A RF Impedance Analyzer (for SRF measurements)
- Wheatstone bridge

DIMENSIONS in inches [millimeters]



* Recommended minimum spacing between components

PART MARKING

- Vishay Dale
- Inductance value
- Date code

DESCRIPTION

IMC-1812 10 μH ± 10 % ER e3
 MODEL INDUCTANCE VALUE INDUCTANCE TOLERANCE PACKAGE CODE JEDEC LEAD FREE STANDARD

GLOBAL PART NUMBER





Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.