# MM3Z2V4ST1 SERIES

# **Zener Voltage Regulators**

## 200 mW SOD-323 Surface Mount **Tight Tolerance Portfolio**

This series of Zener diodes is packaged in a SOD-323 surface mount package that has a power dissipation of 200 mW. They are designed to provide voltage regulation protection and are especially attractive in situations where space is at a premium. They are well suited for applications such as cellular phones, hand-held portables, and high density PC boards.

#### **Specification Features:**

- Standard Zener Breakdown Voltage Range -2.4 V to 18 V
- Steady State Power Rating of 200 mW
- Small Body Outline Dimensions: 0.067" x 0.049" (1.7 mm x 1.25 mm)
- Low Body Height: 0.035" (0.9 mm)
- Package Weight: 4.507 mg/unit
- ESD Rating of Class 3 (>16 kV) per Human Body Model
- Tight Tolerance V<sub>Z</sub>
- Pb–Free Packages are Available

#### **Mechanical Characteristics:**

CASE: Void-free, transfer-molded plastic FINISH: All external surfaces are corrosion resistant MAXIMUM CASE TEMPERATURE FOR SOLDERING PURPOSES: 260°C for 10 Seconds **LEADS:** Plated with Pb–Sn or Sn only (Pb–Free) POLARITY: Cathode indicated by polarity band FLAMMABILITY RATING: UL 94 V-0 **MOUNTING POSITION: Any** 

#### MAXIMUM RATINGS

Rating	Symbol	Max	Unit
Total Device Dissipation FR–5 Board, (Note 1) @ T <sub>A</sub> = 25°C Derate above 25°C	P <sub>D</sub>	200 1.5	mW mW/°C
Thermal Resistance from Junction-to-Ambient	$R_{\thetaJA}$	635	°C/W
Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	-65 to +150	°C

Maximum ratings are those values beyond which device damage can occur. Maximum ratings applied to the device are individual stress limit values (not normal operating conditions) and are not valid simultaneously. If these limits are exceeded, device functional operation is not implied, damage may occur and reliability may be affected.

1. FR-4 Minimum Pad.



## ON Semiconductor<sup>®</sup>

#### http://onsemi.com





M = Date Code

#### **ORDERING INFORMATION**

Device	Package	Shipping <sup>†</sup>
MM3ZxxxST1	SOD-323	3000/Tape & Reel
MM3ZxxxST3	SOD-323	10,000/Tape & Reel
MM3ZxxxST1G	SOD-323 (Pb-Free)	3000/Tape & Reel
MM3ZxxxST3G	SOD-323 (Pb-Free)	10,000/Tape & Reel

+For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

#### **DEVICE MARKING INFORMATION**

See specific marking information in the device marking column of the Electrical Characteristics table on page 2 of this data sheet.

### ELECTRICAL CHARACTERISTICS

(T\_A = 25°C unless otherwise noted, V\_F = 0.9 V Max. @ I\_F = 10 mA for all types)

Symbol	Parameter				
Vz	Reverse Zener Voltage @ I <sub>ZT</sub>				
I <sub>ZT</sub>	Reverse Current				
Z <sub>ZT</sub>	Maximum Zener Impedance @ I <sub>ZT</sub>				
I <sub>ZK</sub>	Reverse Current				
Z <sub>ZK</sub>	Maximum Zener Impedance @ I <sub>ZK</sub>				
I <sub>R</sub>	Reverse Leakage Current @ V <sub>R</sub>				
V <sub>R</sub>	Reverse Voltage				
١ <sub>F</sub>	Forward Current				
VF	Forward Voltage @ I <sub>F</sub>				
ΘVZ	Maximum Temperature Coefficient of $V_Z$				
С	Max. Capacitance $@V_R = 0$ and f = 1 MHz				



#### **ELECTRICAL CHARACTERISTICS** (V<sub>F</sub> = 0.9 Max @ I<sub>F</sub> = 10 mA for all types)

		Test	Zener Vo	ltage VZ	Z <sub>ZK</sub> I <sub>Z</sub> = 0.5	Z <sub>ZT</sub> I <sub>Z</sub> = IZT @ 10%	M IR @	ax 》VR	d <sub>VZ</sub> /dt @ I <sub>ZT1</sub>	(mV/k) = 5 mA	C pF Max @
Device	Device Marking	Current Izt mA	Min	Max	mA Ω Max	Mod Ω Max	μA	v	Min	Max	V <sub>R</sub> = 0 f = 1 MHz
MM3Z2V4ST1	T2	5.0	2.43	2.63	1000	100	120	1.0	-3.5	0	450
MM3Z2V7ST1	Т3	5.0	2.67	2.91	1000	100	100	1.0	-3.5	0	450
MM3Z3V3ST1	T5	5.0	3.32	3.53	1000	95	5.0	1.0	-3.5	0	450
MM3Z3V3TT1, G	ТХ	5.0	3.19	3.41	100	95	5.0	1.0	-3.5	0	450
MM3Z3V6ST1, G	Т6	5.0	3.60	3.85	1000	90	5.0	1.0	-3.5	0	450
MM3Z3V9ST1, G	T7	5.0	3.89	4.16	1000	90	3.0	1.0	-3.5	-2.5	450
MM3Z4V3ST1	Т8	5.0	4.17	4.43	1000	90	3.0	1.0	-3.5	0	450
MM3Z4V7ST1, G	Т9	5.0	4.55	4.75	800	80	3.0	2.0	-3.5	0.2	260
MM3Z5V1ST1	TA	5.0	4.98	5.2	500	60	2.0	2.0	-2.7	1.2	225
MM3Z5V6ST1	TC	5.0	5.49	5.73	200	40	1.0	2.0	-2.0	2.5	200
MM3Z6V2ST1	TE	5.0	6.06	6.33	100	10	3.0	4.0	0.4	3.7	185
MM3Z6V8ST1	TF	5.0	6.65	6.93	160	15	2.0	4.0	1.2	4.5	155
MM3Z7V5ST1	TG	5.0	7.28	7.6	160	15	1.0	5.0	2.5	5.3	140
MM3Z8V2ST1	TH	5.0	8.02	8.36	160	15	0.7	5.0	3.2	6.2	1358
MM3Z9V1ST1	TK	5.0	8.85	9.23	160	15	0.5	6.0	3.8	7.0	130
MM3Z10VST1	WB	5.0	9.80	10.20	160	15	0.5	6.0	4.5	8.0	130
MM3Z11VST1	WC	5.0	10.78	11.22	160	15	0.5	7.0	5.4	9.0	130
MM3Z12VST1	TN	5.0	11.74	12.24	80	25	0.1	8.0	6.0	10	130
MM3Z15VST1*	WF	5.0	14.7	15.3	80	30	0.05	10.5	9.2	13	110
MM3Z16VST1	TU	5.0	15.85	16.51	80	40	0.05	11.2	10.4	14	105
MM3Z18VST1	TW	5.0	17.56	18.35	80	45	0.05	12.6	12.4	16	100

\*Product preview - parts available upon request.

## MM3Z2V4ST1 SERIES

### **Typical Characteristics**



#### MM3Z2V4ST1 SERIES

#### PACKAGE DIMENSIONS

SOD-323 CASE 477-02 ISSUE E





NOTES:

- 1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M. 1982.
- CONTROLLING DIMENSION: MILLIMETERS.
- 3.
- LEAD THICKNESS SPECIFIED PER L/F DRAWING WITH SOLDER PLATING. DIMENSIONS A AND B DO NOT INCLUDE 4. MOLD FLASH, PROTRUSIONS OR GATE BURRS
- DIMENSION L IS MEASURED FROM END OF 5. RADIUS

	MILLIN	IETERS	INCHES			
DIM	MIN	MAX	MIN	MAX		
Α	1.60	1.80	0.063	0.071		
В	1.15	1.35	0.045	0.053		
С	0.80	1.00	0.031	0.039		
D	0.25	0.40	0.010	0.016		
E	0.15	REF	0.006 REF			
н	0.00	0.10	0.000	0.004		
J	0.089	0.177	0.0035	0.0070		
K	2.30	2.70	0.091	0.106		
L	0.075		0.003			

STYLE 1: PIN 1. CATHODE 2. ANODE

#### SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

ON Semiconductor and in the registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights or the rights of others. SCILLC products are not designed, intended, or authorized for use a components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

#### PUBLICATION ORDERING INFORMATION

#### LITERATURE FULFILLMENT:

Literature Distribution Center for ON Semiconductor P.O. Box 61312, Phoenix, Arizona 85082-1312 USA Phone: 480-829-7710 or 800-344-3860 Toll Free USA/Canada Fax: 480-829-7709 or 800-344-3867 Toll Free USA/Canada Email: orderlit@onsemi.com

N. American Technical Support: 800-282-9855 Toll Free USA/Canada

Japan: ON Semiconductor, Japan Customer Focus Center 2-9-1 Kamimeguro, Meguro-ku, Tokyo, Japan 153-0051 Phone: 81-3-5773-3850

ON Semiconductor Website: http://onsemi.com

Order Literature: http://www.onsemi.com/litorder

For additional information, please contact your local Sales Representative.