

MMBTH34 Surface Mount NPN RF-IF Amp


General Description

This device was designed for common-emitter low noise amplifier and mixer applications in the 100 μA to 15 mA range to 300 MHz, and low frequency drift common-base VHF oscillator applications with high output levels for driving FET mixers.

Absolute Maximum Ratings

Collector-Base Voltage	45V
Emitter-Base Voltage	4.0V
Collector Current—Continuous	100 mA
Total Device Dissipation, $T_A = 25^\circ\text{C}$	350°C
Derate above 25°C (Note 1)	2.8 mW/°C
Operating Temperature Range	-55°C to +150°C
Storage Temperature Range	-55°C to +150°C
Lead Temperature for 10 seconds	300°C

Note 1: Package mounted on 99.5% alumina 10 x 8 x 0.6 mm.




Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise specified

Symbol	Conditions	Min	Typ	Max	Units
BV_{CBO}	$I_C = 100 \mu\text{A}$	45			V
BV_{CEO}	$I_C = 1.0 \text{ mA}$	45			V
BV_{EBO}	$I_E = 10 \mu\text{A}$	4.0			V
I_{CBO}	$V_{CB} = 30\text{V}$			50	nA
I_{CES}	$V_{CE} = 30\text{V}$			50	nA
h_{FE}	$V_{CE} = 15\text{V}, I_C = 7.0 \text{ mA}$	40			
h_{FE}	$V_{CE} = 2.0\text{V}, I_C = 20 \text{ mA}$	15			
$V_{CE(s)}$	$I_C = 20 \text{ mA}, I_B = 2.0 \text{ mA}$			0.5	V
$V_{BE(on)}$	$V_{CE} = 15\text{V}, I_C = 7.0 \text{ mA}$			0.95	V
C_{cb}	$V_{CB} = 10\text{V}, f = 1 \text{ MHz}$			0.32	pF
h_{fe}	$V_{CE} = 15\text{V}, I_C = 15 \text{ mA}, f = 100 \text{ MHz}$	5.0			

Order Number **MMBTH34** or **MMBTH34-HIGH**
See NS Package Number **M03**

Physical Dimensions inches (millimeters)



SOT-23 3-Lead Molded Dual-In-Line (M)
Order Number MMBTH34 or MMBTH34-HIGH
NS Package Number M03

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.



National Semiconductor Corporation
 1111 West Bardin Road
 Arlington, TX 76017
 Tel: 1(800) 272-9959
 Fax: 1(800) 737-7018

National Semiconductor Europe
 Fax: (+49) 0-180-530 85 86
 Email: cnjwge@tevm2.nsc.com
 Deutsch Tel: (+49) 0-180-530 85 85
 English Tel: (+49) 0-180-532 78 32
 Français Tel: (+49) 0-180-532 93 58
 Italiano Tel: (+49) 0-180-534 16 80

National Semiconductor Hong Kong Ltd.
 19th Floor, Straight Block,
 Ocean Centre, 5 Canton Rd.
 Tsimshatsui, Kowloon
 Hong Kong
 Tel: (852) 2737-1600
 Fax: (852) 2736-9960

National Semiconductor Japan Ltd.
 Tel: 81-043-299-2309
 Fax: 81-043-299-2408

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.