

- ◆ P-Channel Power MOS FET
- ◆ DMOS Structure
- ◆ Low On-State Resistance: **0.48Ω MAX**
- ◆ Ultra High-Speed Switching
- ◆ SOT-23 Package

### Applications

- Notebook PCs
- Cellular and portable phones
- On-board power supplies
- Li-ion battery systems

### General Description

The XP152A01D8MR is a P-Channel Power MOS FET with low on-state resistance and ultra high-speed switching characteristics. Because high-speed switching is possible, the IC can be efficiently set thereby saving energy. The small SOT-23 package makes high density mounting possible.

### Features

**Low on-state resistance:**  $R_{ds(on)}=0.48\Omega(V_{gs}=-4.5V)$   
 $R_{ds(on)}=0.80\Omega(V_{gs}=-2.5V)$


**Ultra high-speed switching**

**Operational Voltage:** -2.5V

**High density mounting:** SOT-23

7


### Pin Configuration



### Pin Assignment

PIN NUMBER	PIN NAME	FUNCTION
1	G	Gate
2	S	Source
3	D	Drain

### Equivalent Circuit



### Absolute Maximum Ratings

$T_a=25^\circ\text{C}$

PARAMETER	SYMBOL	RATINGS	UNITS
Drain-Source Voltage	$V_{dss}$	-20	V
Gate-Source Voltage	$V_{gss}$	$\pm 12$	V
Drain Current (DC)	$I_d$	-0.5	A
Drain Current (Pulse)	$I_{dp}$	-1.5	A
Reverse Drain Current	$I_{dr}$	-0.5	A
Continuous Channel Power Dissipation (note)	$P_d$	0.5	W
Channel Temperature	$T_{ch}$	150	$^\circ\text{C}$
Storage Temperature	$T_{stg}$	-55~150	$^\circ\text{C}$

Note: When implemented on a glass epoxy PCB

## Electrical Characteristics

### DC characteristics

Ta=25°C

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Drain Cut-off Current	Idss	Vds=-20V, Vgs=0V			-10	μA
Gate-Source Leakage Current	Igss	Vgs=±12V, Vds=0V			±10	μA
Gate-Source Cut-off Voltage	Vgs(off)	Id=-1mA, Vds=-10V	-0.5			V
Drain-Source On-state Resistance (note)	Rds(on)	Id=-0.3A, Vgs=-4.5V		0.36	0.48	Ω
		Id=-0.3A, Vgs=-2.5V		0.6	0.8	Ω
Forward Transfer Admittance (note)	Yfs	Id=-0.3A, Vds=-10V		1		S
Body Drain Diode Forward Voltage	Vf	If=-0.5A, Vgs=0V		-0.8	-1.1	V

Note: Effective during pulse test.

### Dynamic characteristics

Ta=25°C

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Input Capacitance	Ciss	Vds=-10V, Vgs=0V f=1MHz		180		pF
Output Capacitance	Coss			100		pF
Feedback Capacitance	Crss			35		pF

### Switching characteristics

Ta=25°C


PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Turn-on Delay Time	td (on)	Vgs=-5V, Id=-0.3A Vdd=-10V		10		ns
Rise Time	tr			15		ns
Turn-off Delay Time	td (off)			30		ns
Fall Time	tf			70		ns

### Thermal characteristics


PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
Thermal Resistance (channel-surroundings)	Rth (ch-a)	Implement on a glass epoxy resin PCB		250		°C/W

### XP152A01D8MR Characteristics


Drain Current vs. Drain /Source Voltage




Drain Current vs. Gate/Source Voltage




Drain/Source On-State Resistance vs. Gate/Source Voltage




Drain/Source On-State Resistance vs. Drain Current



Drain/Source On-State Resistance vs. Ambient Temp.




Gate/Source Cut Off Voltage Variance vs. Ambient Temp.




7

## XP152A01D8MR Characteristics


Drain/Source Voltage vs. Capacitance




Switching Time vs. Drain Current



Gate/Source Voltage vs. Gate Charge



Reverse Drain Current vs. Source/Drain Voltage



Standardized Transition Thermal Resistance vs. Pulse Width

