


### PNP Silicon High-Voltage Transistor

- High breakdown voltage
- Low collector-emitter saturation voltage
- Complementary type: SMBTA 42M (NPN)



Type	Marking	Ordering Code	Pin Configuration					Package
SMBTA 92M	s2D	Q62702-A1244	1 = B	2 = C	3 = E	4=n.c.	5 = C	SCT-595

#### Maximum Ratings

Parameter	Symbol	Value	Unit
Collector-emitter voltage	$V_{CEO}$	300	V
Collector-base voltage	$V_{CBO}$	300	
Emitter-base voltage	$V_{EBO}$	5	
DC collector current	$I_C$	500	mA
Base current	$I_B$	100	
Total power dissipation, $T_S \leq 83\text{ °C}$	$P_{tot}$	1.5	W
Junction temperature	$T_j$	150	°C
Storage temperature	$T_{stg}$	- 65...+150	

#### Thermal Resistance

Junction ambient <sup>1)</sup>	$R_{thJA}$	$\leq 100$	K/W
Junction - soldering point	$R_{thJS}$	$\leq 45$	

1) Package mounted on pcb 40mm x 40mm x 1.5mm / 6cm<sup>2</sup> Cu


**Electrical Characteristics** at  $T_A = 25^\circ\text{C}$ , unless otherwise specified.

Parameter	Symbol	Values			Unit
		min.	typ.	max.	
<b>DC characteristics</b>					
Collector-emitter breakdown voltage $I_C = 100 \mu\text{A}, I_B = 0$	$V_{(BR)CEO}$	300	-	-	V
Collector-base breakdown voltage $I_C = 100 \mu\text{A}, I_B = 0$	$V_{(BR)CBO}$	300	-	-	
Emitter-base breakdown voltage $I_E = 10 \mu\text{A}, I_C = 0$	$V_{(BR)EBO}$	5	-	-	
Collector cutoff current $V_{CB} = 200 \text{V}, I_E = 0$	$I_{CBO}$	-	-	250	nA
Collector-base cutoff current $V_{CB} = 200 \text{V}, T_A = 150^\circ\text{C}$	$I_{CBO}$	-	-	20	$\mu\text{A}$
Emitter cutoff current $V_{EB} = 3 \text{V}, I_C = 0$	$I_{EBO}$	-	-	100	nA
DC current gain 1) $I_C = 1 \text{mA}, V_{CE} = 10 \text{V}$ $I_C = 10 \text{mA}, V_{CE} = 10 \text{V}$ $I_C = 30 \text{mA}, V_{CE} = 10 \text{V}$	$h_{FE}$	25 40 25	- - -	- - -	-
Collector-emitter saturation voltage 1) $I_C = 20 \text{mA}, I_B = 2 \text{mA}$	$V_{CEsat}$	-	-	0.5	V
Base-emitter saturation voltage 1) $I_C = 20 \text{mA}, I_B = 2 \text{mA}$	$V_{BEsat}$	-	-	0.9	
<b>AC Characteristics</b>					
Transition frequency $I_C = 10 \text{mA}, V_{CE} = 20 \text{V}, f = 100 \text{MHz}$	$f_T$	50	-	-	MHz
Collector-base capacitance $V_{CB} = 20 \text{V}, f = 1 \text{MHz}$	$C_{cb}$	-	-	6	pF

1) Pulse test:  $t < 300 \mu\text{s}; D < 2\%$


### Total power dissipation $P_{tot} = f(T_A^*; T_S)$

\* Package mounted on epoxy




### DC current gain $h_{FE} = f(I_C)$

$V_{CE} = 10V$




### Permissible Pulse Load $R_{thJS} = f(t_p)$




### Permissible Pulse Load

$P_{totmax} / P_{totDC} = f(t_p)$



**Collector cutoff current  $I_{CBO} = f(T_A)$**

$V_{CB} = 160V$



**Collector current  $I_C = f(V_{BE})$**

$V_{CE} = 10V$

