

**SURFACE MOUNT
GLASS PASSIVATED RECTIFIER**

**REVERSE VOLTAGE – 400 to 1000 Volts
FORWARD CURRENT – 2.0 Ampere**


FEATURES

- Glass passivated chip
- For surface mounted applications
- Low reverse leakage current
- Low forward voltage drop
- High current capability

MECHANICAL DATA

- Case: Molded plastic
- Polarity: Indicated by cathode band
- Terminals: Solder plated copper
- Weight: 0.002 ounce, 0.064 grams

SMA



SMA		
DIM.	MIN.	MAX.
A	4.06	4.57
B	2.29	2.92
C	1.27	1.63
D	0.15	0.31
E	4.83	5.59
F	0.05	0.20
G	2.01	2.40
H	0.76	1.52

All dimension in millimeter

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

PARAMETER	SYMBOL	S2GHA	S2JHA	S2KHA	S2MHA	UNIT
Device marking code	Note	S2GHA	S2JHA	S2KHA	S2MHA	---
Maximum Repetitive Peak Reverse Voltage	V_{RRM}	400	600	800	1000	V
Maximum RMS Voltage	V_{RMS}	280	420	560	700	V
Maximum DC Blocking Voltage	V_{DC}	400	600	800	1000	V
Average Rectified Output Current @ $T_L=90^\circ C$	$I_{(AV)}$	2.0				A
Peak Forward Surge Current 8.3ms single half sine-wave	I_{FSM}	50				A
Operating junction temperature range	T_J	-55 to +150				°C
Storage temperature range	T_{STG}	-55 to +150				°C
PARAMETER	TEST CONDITIONS	SYMBOL	Max.			UNIT
Forward Voltage (1)	$I_F=2.0A$ $T_j=25^\circ C$	V_F	1.15			V
Leakage Current (1)	$V_R=V_{DC}$ $T_j=25^\circ C$ $T_j=125^\circ C$	I_R	5 125			uA
THERMAL CHARACTERISTIC		SYMBOL	Typical			UNIT
Typical junction capacitance (2)		C_J	10			pF
Typical thermal resistance _ Junction to Case (3)		$R_{\theta JC}$	21			°C/W
Typical thermal resistance _ Junction to Ambient (3)		$R_{\theta JA}$	58			°C/W
Typical thermal resistance _ Junction to Lead (3)		$R_{\theta JL}$	33			°C/W

Note :

- (1) 300us Pulse width, 2% Duty cycle.
- (2) Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
- (3) Thermal Resistance test performed in accordance with JESD-51. Unit mounted on 0.75t glass-epoxy substrate with 10mmx10mm copper pad. $R_{\theta JL}$ is measured at the lead of cathode band, $R_{\theta JC}$ is measured at the top centre of body.

REV. 0, Apr-2010, KSDA05

FIG.1- FORWARD CURRENT DERATING CURVE




FIG.2- MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3- TYPICAL FORWARD CHARACTERISTICS




FIG.4- TYPICAL JUNCTION CAPACITANCE





FIG.5- TYPICAL REVERSE CHARACTERISTICS



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.